



57832 County Road 3 • Elkhart, IN 46517 • Ph: 574.295.3166 • Email: GriffinTrailer@gmail.com

CUSTOMER PRODUCT DELIVERY OVERVIEW

- <https://www.GriffinTrailer.com/warranty-registration/>  
Register your new Griffin Trailer not later than \_\_\_\_\_ to ensure your warranty will be honored. (10 days from date of sale)
- <https://www.GriffinTrailer.com/downloadable-documents/>  
Visit the downloads page to receive a copy of your Owners Manual. Entirely reviewing the Owners Manual should be done before using your new trailer.
- Do a visual inspection of your trailer prior to use each time. Look for potential evidence of tampering or damage which may have altered things like wheel lugs, coupler lock, ramp pins, etc.
- Maintain a full charge of the trailer 12v battery when stored as your vehicle will not charge it just because it is connected to the brake wire harness.
- In case the hydraulic system is not operating properly, do not attempt to repair, alter, or adjust any components on your own. Improper adjustments, replacement of parts, or any other modifications could result in serious injury or even death. Take the trailer to the nearest Griffin Dealer for immediate attention before using the hydraulic function further.
- Ramps are rated for a total combined weight capacity of 5000lbs. for both ramps, not each ramp.
- Your trailer has specifically located warning and usage stickers that must be heeded. Should any become faded or damaged, replacements may be attained using the contact form on the website or by calling, 574.295.3166. In addition, the owners manual may provide more specific details about safe usage of your new trailer and you are encouraged to be familiar with those sections as well.
- In case of warranty related work needing performed, refer to the sticker inside the pump housing at the front of the trailer or contact your nearest Griffin Dealer.
- When loading trailer, distribute weight evenly over entire bed area to avoid tipping or slippage of contents during transit.
- After taking delivery of your new Griffin Trailer, the wheel lug nuts must be retorqued after 30 miles of transit to ensure safe use.

I have been read and explained these product overview details by my Griffin Dealer representative and acknowledge so by providing my signature and information below.

DATE: \_\_\_\_\_ LAST 6 OF TRAILER VIN: 

--	--	--	--	--	--

RETAIL BUYER NAME: \_\_\_\_\_

RETAIL BUYER SIGNATURE: \_\_\_\_\_

DEALER REPRESENTATIVE NAME: \_\_\_\_\_

DEALER REPRESENTATIVE SIGNATURE: \_\_\_\_\_